



LUBRICANT

SLIPPING AGENT FOR PIPE SYSTEMS WITH RUBBER SLEEVE CONNECTIONS



Stains/residue: Remove residues with a degreaser.

TECHNICAL PROPERTIES

Temperature resistance: -20°C - +45°C

TECHNICAL SPECIFICATIONS

Chemical base: Acid-free vaseline

Colour: White

Viscosity: approx. Pasty

Density: approx. 0.81 g/cm³

STORAGE CONDITIONS

Minimum of 24 months if stored in properly sealed packaging in a dry place at a temperature between +5°C and +25°C. Limited shelf life after opening.

PRODUCT DESCRIPTION

Slipping agent for pipe systems with rubber sleeve connections.

FIELD OF APPLICATION

For assembling pipes, sleeves and fittings with rubber sleeve (sliding socket) connections in drain systems. Suitable for all diameters. Suitable for PVC-U, ABS, PE, PP, GRP, concrete and coated cast iron.

PROPERTIES

- Re-adjustable
- Acid-free
- Thixotropic

PREPARATION

Working conditions: Do not use in temperatures $\leq +0^{\circ}\text{C}$.

APPLICATION

Coverage: Indication of the number of joints per 1 L:

Ø	32	40	50	75	90	110	160	250
#	900	600	400	200	135	90	45	20

Directions for use:

1. Saw off pipes squarely, chamfer and deburr.
2. Remove dirt and moisture.
3. Apply slipping agent to pipe end and rubber sleeve.
4. Join parts immediately by sliding the tube into the sliding socket until the stopper. Joint is easily adjustable. Properly close the container immediately after use.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.